

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **B A ; N P R E M I U M 0 W - 5 0**
CHEMICAL NAME: Synthetic Oil, Additives
CAS REGISTRY NO: INDUSTRIAL SECRETS
MANUFACTURER: Kygnus Sekiyu K.K.
Nittobo Bldg., 2-8-1 Yaesu Chuo-ku,
Tokyo JAPAN 104-8455
Tel: 3-3276-5240
Fax: 3-3276-5391

2. HAZARDS IDENTIFICATION OF THE PRODUCT

***** EMERGENCY OVERVIEW *****

Not expected to cause a severe emergency hazard.

Using this product as gasoline engine oil, the used oil may have carcinogenicity.

PRIMARY ENTRY ROUTES : Skin

INHALATION -----

Inhalation of vapor or mist may result in dizziness and nausea.

SKIN -----

Prolonged and/or repeated contact may cause skin irritation and inflammation.

EYE -----

Contact with the eye may cause irritation and redness.

INGESTION -----

Ingestion may result in nausea and/or diarrhea.

Acute toxicity : LD50 > 5g/Kg

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE -----

Personnel with pre-existing skin disorders should avoid contact with this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synthetic Oil	more than	70 [wt%]
Additives	less than	30 [wt%]

This ingredients in this product are on TSCA Inventory and in CAS.

4. FIRST AID MEASURES

EYE -----

Flush with large amounts of water for at least 15 minutes.

If redness or irritation persists, contact a physician.

SKIN -----

Wash with soap and water. Wash clothing before reuse.

If irritation or rash develops, obtain medical assistance.

INGESTION -----

Do not induce vomiting ! Call a physician.

INHALATION -----

Move to fresh air.
Keep a victim warm by covering with a blanket and in quiet.
Assist breathing if necessary. Contact a physician.

5. FIRE FIGHTING MEASURES

SPECIFIC HAZARD

--- FLAMMABLE LIMITS IN AIR ---

LOWER EXPLOSIVE LIMIT (LEL) ...: N/D % VOL.
UPPER EXPLOSIVE LIMIT (UEL) ...: N/D % VOL.

FLASH POINT.....: > 200°C (COC)
AUTOIGNITION TEMP.....: N/D

--- NFPA CLASSIFICATION ---

HEALTH - 1
FIRE - 1
REACTIVITY - 0

---- HAZARD RATING ----

0 - LEAST 3 - HIGH
1 - SLIGHT 4 - EXTREME
2 - MODERATE

FIRE AND EXPLOSION HAZARDS -----

Can be made to burn.

EXTINGUISHING MEDIA -----

Halon Dry Chemical, CO₂, Foam, Water Mist or fog.

SPECIAL FIRE FIGHTING INSTRUCTIONS -----

Wear self-contained breathing apparatus. Do not use forced stream as this could cause fire to spread.

6. ACCIDENTAL RELEASE MEASURES

SPILL/LEAK PROCEDURES -----

Stop spill at source if possible without risk. Contain spill. Eliminate sources of ignition. Spill area Will be slick. Recover all possible material for reclamation. Use non-flammable absorbent material to pick up remainder of spill.

7. HANDLING AND STORAGE

HANDLING AND STORAGE -----

Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty oil containers can contain explosive vapor.
NFPA Class III B storage. Wash thoroughly after handling.

WORK/HYGIENIC PRACTICES -----

Wash hand with soap and water before eating, drinking, smoking or use of toilet facilities. Do not use gasoline, solvent, kerosene, or harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove oil-soaked clothing and launder before reuse.
Launder or discard contaminated shoes and leather gloves.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS -----

5[mg/m³] mineral oil mist (ACGIH 8 hour TWA)

ENGINEERING CONTROLS -----

Use adequate ventilation to keep oil mists of this material below applicable standard(s).
See section on occupational exposure limits

EYE/FACE PROTECTION -----

Safety glasses or splash goggles. Have suitable eye wash water available.

SKIN PROTECTION -----

Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective impervious gloves and clothing.
Acceptable materials for gloves are polyvinyl chloride; neoprene; nitrile; polyvinyl alcohol; viton.

RESPIRATORY PROTECTION -----

Normally not required if adequate ventilation.
NIOSH/MSHA approved apparatus

OTHER/GENERAL PROTECTION -----

If there is a likelihood of splashing, an oil resistant clothing should be worn. Never wear oil soaked clothing. Launder or dry clean before wearing. Discard oil soaked shoes.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT	Wide Range
MELTING POINT	N/A
SPECIFIC GRAVITY	0.84
PACKING DENSITY	N/A
VAPOR PRESSURE	< 0.03 ([Pa] at 25°C)
VAPOR DENSITY	> 10 (AIR=1)
SOLUBILITY IN WATER	Insoluble
PH INFORMATION	N/A
% VOLATILES BY VOL	Negligible
EVAPORATION RATE	Negligible
OCTANOL / WATER COEFF	N/D
APPEARANCE	Yellow Liquid
ODOR	Slight Odor
ODOR THRESHOLD	N/D

10. STABILITY AND REACTIVITY

STABILITY -----

Stable

CONDITIONS TO AVOID (STABILITY) -----

Sources of ignition.

INCOMPATIBLE MATERIALS -----

Strong oxidizing agents such as chromic acid, hydrogen peroxide and bromine.

HAZARDOUS DECOMPOSITION PRODUCTS -----

Upon combustion, CO₂ and CO are generated.

HAZARDOUS POLYMERIZATION -- -----

Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

ACUTE STUDIES -----

Tests on similar materials show a low order of acute oral and dermal toxicity.

【BA;N PREMIUM 0W-50】 MATERIAL SAFETY DATA SHEET

EYE EFFECTS -----

Minimal irritation on contact.

SKIN EFFECTS -----

Practically non-toxic if absorbed.

May cause mild irritation with prolonged and repeated contact.

ACUTE ORAL EFFECTS -----

Tests on similar materials indicate low order of acute oral toxicity.

ACUTE INHALATION EFFECTS -----

Low acute toxicity expected on inhalation.

12. ECOLOGICAL INFORMATION

AQUATIC RELEASE -----

Advise authorities if product has entered or may enter watercourses or sewer drains.

13. DISPOSAL CONSIDERATIONS

SPILL, LEAK OR RELEASE -----

Stop leak, dike up large spills. Use inert absorbent material such as earth, sand, or vermiculite for clean-up.

WASTE DISPOSAL METHOD -----

Dispose of in accordance with Local, State, and Federal government regulations.

14. TRANSPORT INFORMATION

Proper Shipping Name : Not regulated by DOT (Contains oil)
Hazard Class : Not Applicable
DOT ID No. : Not Applicable
DOT Shipping Label : Not regulated by DOT
Usual Shipping Containers : Rail cars, Tank truck, Drums.
Transport Temperature Deg.C: Ambient to max 60 °C

15. REGULATORY INFORMATION

U.S.FEDERAL REGULATORY INFORMATION -----

SARA 302 Threshold Planning Quantity : N/A
SARA 304 Reportable Quantity : N/A
SARA 311 Categories : Immediate (Acute) Health Effects -- No
Delayed (Chronic) Health Effects -- No
Fire Hazard -- No
Sudden Release of pressure Hazard -- No
Reactivity Hazard -- No

Comprehensive Environmental Response, Compensation and liability Act (CERCLA) -----

No chemicals in this product are subject to the reporting requirements of CERCLA.

16. OTHER INFORMATION

DISCLAIMER -----

The information contained herein is based upon data believed to be Reliable and reflects our best professional judgment.

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein and assume no responsibility regarding the suitability of this information for the user's intended purpose or for the consequence of its use.

Each individual should make a determination as to the suitability of the information for his/her particular purpose(s).